
NSEntityDescription Class Reference

Data Management



2009-05-01



Apple Inc.
© 2009 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Mac, Mac OS, and Xcode are trademarks of Apple Inc., registered in the United States and other countries.

iPhone is a trademark of Apple Inc.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR

CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

NSEntityDescription Class Reference 5

Overview	5
Editing Entity Descriptions	6
Using Entity Descriptions in Dictionaries	6
Fast Enumeration	6
Tasks	6
Information About an Entity Description	6
Managing Inheritance	7
Working with Properties	7
Retrieving an Entity with a Given Name	8
Creating a New Managed Object	8
Supporting Versioning	8
Copying Entity Descriptions	8
Class Methods	8
entityForName:inManagedObjectContext:	8
insertNewObjectForEntityForName:inManagedObjectContext:	9
Instance Methods	11
attributesByName	11
copy	11
isAbstract	11
isKindOfEntity:	12
managedObjectClassName	12
managedObjectModel	13
name	13
properties	13
propertiesByName	14
relationshipsByName	14
relationshipsWithDestinationEntity:	15
renamingIdentifier	15
setAbstract:	16
setManagedObjectClassName:	16
setName:	17
setProperty:	17
setRenamingIdentifier:	18
setSubentities:	18
setUserInfo:	18
setVersionHashModifier:	19
subentities	19
subentitiesByName	20
superentity	20
userInfo	20

versionHash 21
versionHashModifier 21

Document Revision History 23

Index 25

NSEntityDescription Class Reference

Inherits from	NSObject
Conforms to	NSCoding NSCopying NSFastEnumeration NSObject (NSObject)
Framework	/System/Library/Frameworks/CoreData.framework
Availability	Available in Mac OS X v10.4 and later.
Declared in	NSEntityDescription.h
Companion guides	Core Data Programming Guide Core Data Utility Tutorial
Related sample code	Core Data HTML Store CoreRecipes CustomAtomicStoreSubclass Departments and Employees QTMetadataEditor

Overview

Instances of `NSEntityDescription` are used to describe entities in terms of their name, their properties—attributes and relationships as expressed by `NSAttributeDescription` and `NSRelationshipDescription`—and the class by which they are represented. Entities are to managed objects what `Class` is to `id`, or—to use a database analogy—what tables are to rows.

An `NSEntityDescription` object is associated with a specific class whose instances are used to represent entries in a persistent store in applications using the Core Data Framework. Minimally, an entity description should have:

- A name
- The name of a managed object class

(If an entity has no managed object class name, it defaults to `NSManagedObject`.)

You usually define entities in an `NSManagedObjectContext` using the data modeling tool in Xcode. `NSEntityDescription` objects are primarily used by the Core Data Framework for mapping entries in the persistent store to managed objects in the application. You are not likely to interact with them directly unless

you are specifically working with models. Like the other major modeling classes, `NSEntityDescription` provides you with a user dictionary in which you can store any application-specific information related to the entity.

Editing Entity Descriptions

Entity descriptions are editable until they are used by an object graph manager. This allows you to create or modify them dynamically. However, once a description is used (when the managed object model to which it belongs is associated with a persistent store coordinator), it *must not* (indeed cannot) be changed. This is enforced at runtime: any attempt to mutate a model or any of its sub-objects after the model is associated with a persistent store coordinator causes an exception to be thrown. If you need to modify a model that is in use, create a copy, modify the copy, and then discard the objects with the old model.

If you want to create an entity hierarchy, you need to consider the relevant API. You can only set an entity's sub-entities (see `setSubentities:` (page 18)), you cannot set an entity's super-entity directly. To set a super-entity for a given entity, you must therefore set an array of subentities on that super entity and include the current entity in that array. So, the entity hierarchy needs to be built top-down.

Using Entity Descriptions in Dictionaries

`NSEntityDescription`'s `copy` (page 11) method returns an entity such that

```
[[entity copy] isEqual: entity] == NO
```

Since `NSDictionary` copies its keys and requires that keys both conform to the `NSCopying` protocol and have the property that `copy` returns an object for which `[[object copy] isEqual:object]` is true, you should not use entities as keys in a dictionary. Instead, you should either use the entity's name as the key, or use a map table (`NSMutableDictionary`) with retain callbacks.

Fast Enumeration

In Mac OS v10.5 and later and on iPhone OS, `NSEntityDescription` supports the `NSFastEnumeration` protocol. You can use this to enumerate over an entity's properties, as illustrated in the following example:

```
NSEntityDescription *anEntity = ...;
for (NSPropertyDescription *property in anEntity)
{
    // property is each instance of NSPropertyDescription in anEntity in turn
}
```

Tasks

Information About an Entity Description

- `name` (page 13)
Returns the entity name of the receiver.

- [setName:](#) (page 17)
Sets the entity name of the receiver.
- [managedObjectModel](#) (page 13)
Returns the managed object model with which the receiver is associated.
- [managedObjectClassName](#) (page 12)
Returns the name of the class that represents the receiver's entity.
- [setManagedObjectClassName:](#) (page 16)
Sets the name of the class that represents the receiver's entity.
- [renamingIdentifier](#) (page 15)
Returns the renaming identifier for the receiver.
- [setRenamingIdentifier:](#) (page 18)
Sets the renaming identifier for the receiver.
- [isAbstract](#) (page 11)
Returns a Boolean value that indicates whether the receiver represents an abstract entity.
- [setAbstract:](#) (page 16)
Sets whether the receiver represents an abstract entity.
- [userInfo](#) (page 20)
Returns the user info dictionary of the receiver.
- [setUserInfo:](#) (page 18)
Sets the user info dictionary of the receiver.

Managing Inheritance

- [subentitiesByName](#) (page 20)
Returns the sub-entities of the receiver in a dictionary.
- [subentities](#) (page 19)
Returns an array containing the sub-entities of the receiver.
- [setSubentities:](#) (page 18)
Sets the subentities of the receiver.
- [superentity](#) (page 20)
Returns the super-entity of the receiver.
- [isKindOfEntity:](#) (page 12)
Returns a Boolean value that indicates whether the receiver is a subentity of another given entity.

Working with Properties

- [propertiesByName](#) (page 14)
Returns a dictionary containing the properties of the receiver.
- [properties](#) (page 13)
Returns an array containing the properties of the receiver.
- [setProperty:](#) (page 17)
Sets the properties array of the receiver.

- [attributesByName](#) (page 11)
Returns the attributes of the receiver in a dictionary, where the keys in the dictionary are the attribute names.
- [relationshipsByName](#) (page 14)
Returns the relationships of the receiver in a dictionary, where the keys in the dictionary are the relationship names.
- [relationshipsWithDestinationEntity:](#) (page 15)
Returns an array containing the relationships of the receiver where the entity description of the relationship is a given entity.

Retrieving an Entity with a Given Name

- + [entityForName:inManagedObjectContext:](#) (page 8)
Returns the entity with the specified name from the managed object model associated with the specified managed object context's persistent store coordinator.

Creating a New Managed Object

- + [insertNewObjectForEntityForName:inManagedObjectContext:](#) (page 9)
Creates, configures, and returns a new autoreleased instance of the class for the entity with a given name.

Supporting Versioning

- [versionHash](#) (page 21)
Returns the version hash for the receiver.
- [versionHashModifier](#) (page 21)
Returns the version hash modifier for the receiver.
- [setVersionHashModifier:](#) (page 19)
Sets the version hash modifier for the receiver.

Copying Entity Descriptions

- [copy](#) (page 11)
Returns a copy of the receiver

Class Methods

entityForName:inManagedObjectContext:

Returns the entity with the specified name from the managed object model associated with the specified managed object context's persistent store coordinator.

```
+ (NSEntityDescription *)entityForName:(NSString *)entityName
  inManagedObjectContext:(NSManagedObjectContext *)context
```

Parameters

entityName

The name of an entity.

context

The managed object context to use.

Return Value

The entity with the specified name from the managed object model associated with *context's* persistent store coordinator.

Discussion

This method is functionally equivalent to the following code example.

```
NSManagedObjectContext *managedObjectContext = [[context persistentStoreCoordinator]
  managedObjectContext];
NSEntityDescription *entity = [[managedObjectContext entitiesByName]
  objectForKey:entityName];
return entity;
```

Availability

Available in Mac OS X v10.4 and later.

See Also

- `entitiesByName`

Related Sample Code

Core Data HTML Store

CoreRecipes

Departments and Employees

QTMetadataEditor

Declared In

NSEntityDescription.h

insertNewObjectForEntityForName:inManagedObjectContext:

Creates, configures, and returns a new autoreleased instance of the class for the entity with a given name.

```
+ (id)insertNewObjectForEntityForName:(NSString *)entityName
  inManagedObjectContext:(NSManagedObjectContext *)context
```

Parameters

entityName

The name of an entity.

context

The managed object context to use.

Return Value

A new, autoreleased, fully configured instance of the class for the entity named *entityName*. The instance has its entity description set and is inserted it into *context*.

Discussion

Note that despite the word “new” in the method name, the object returned is autoreleased (“new” is not the first word in the method name—see [Memory Management Rules](#)).

This method makes it easier for you to create instances of a given entity without having to know the class used to represent the entity, which may be particularly useful early in the development life-cycle when classes and class names are volatile. It also takes care of the details of managed object creation.

This method makes it easier for you to create instances of a given entity without worrying about the details of managed object creation when there is no need to explicitly assign a new managed object to a specific persistent store.

This is particularly useful on Mac OS X v10.4 as you can use this method to create a new managed object without having to know the class used to represent the entity, especially early in the development life-cycle when classes and class names are volatile. The method is conceptually similar to the following code example.

```

NSManagedObjectModel *managedObjectModel =
    [[context persistentStoreCoordinator] managedObjectModel];
NSEntityDescription *entity =
    [[managedObjectModel entitiesByName] objectForKey:entityName];
NSString *className = [entity managedObjectClassName];
Class entityClass = [[NSBundle mainBundle] classNamed:className];
id newObject = [[entityClass alloc]
    initWithEntity:entity insertIntoManagedObjectContext:context];
return [newObject autorelease];

```

On Mac OS X v10.5 and later and on iPhone OS, `initWithEntity:insertIntoManagedObjectContext:` returns an instance of the appropriate class for the entity. The equivalent code for Mac OS X v10.5 and on iPhone OS is as follows:

```

NSManagedObjectModel *managedObjectModel =
    [[context persistentStoreCoordinator] managedObjectModel];
NSEntityDescription *entity =
    [[managedObjectModel entitiesByName] objectForKey:entityName];
NSManagedObject *newObject = [[NSManagedObject alloc]
    initWithEntity:entity insertIntoManagedObjectContext:context];
return [newObject autorelease];

```

Availability

Available in Mac OS X v10.4 and later.

See Also

- `initWithEntity:insertIntoManagedObjectContext:`

Related Sample Code

CoreRecipes

Departments and Employees

QTMetadataEditor

Declared In

NSEntityDescription.h

Instance Methods

attributesByName

Returns the attributes of the receiver in a dictionary, where the keys in the dictionary are the attribute names.

```
- (NSDictionary *)attributesByName
```

Return Value

The attributes of the receiver in a dictionary, where the keys in the dictionary are the attribute names and the values are instances of `NSAttributeDescription`.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [propertiesByName](#) (page 14)
- [relationshipsByName](#) (page 14)
- [relationshipsWithDestinationEntity:](#) (page 15)

Related Sample Code

Core Data HTML Store
CoreRecipes
CustomAtomicStoreSubclass

Declared In

`NSEntityDescription.h`

copy

Returns a copy of the receiver

```
- (id)copy
```

Return Value

A copy of the receiver.

Special Considerations

`NSEntityDescription`'s implementation of `copy` returns an entity such that:

```
[[entity copy] isEqual:entity] == NO
```

You should not, therefore, use an entity as a key in a dictionary (see [“Using Entity Descriptions in Dictionaries”](#) (page 6)).

isAbstract

Returns a Boolean value that indicates whether the receiver represents an abstract entity.

```
- (BOOL)isAbstract
```

Return Value

YES if the receiver represents an abstract entity, otherwise NO.

Discussion

An abstract entity might be Shape, with concrete sub-entities such as Rectangle, Triangle, and Circle.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [setAbstract:](#) (page 16)

Declared In

NSEntityDescription.h

isKindOfEntity:

Returns a Boolean value that indicates whether the receiver is a subentity of another given entity.

```
- (BOOL)isKindOfEntity:(NSEntityDescription *)entity
```

Parameters

entity

An entity.

Return Value

YES if the receiver is a sub-entity of *entity*, otherwise NO.

Availability

Available in Mac OS X v10.5 and later.

Declared In

NSEntityDescription.h

managedObjectClassName

Returns the name of the class that represents the receiver's entity.

```
- (NSString *)managedObjectClassName
```

Return Value

The name of the class that represents the receiver's entity.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [setManagedObjectClassName:](#) (page 16)

Declared In

NSEntityDescription.h

managedObjectModel

Returns the managed object model with which the receiver is associated.

```
- (NSManagedObjectModel *)managedObjectModel
```

Return Value

The managed object model with which the receiver is associated.

Availability

Available in Mac OS X v10.4 and later.

See Also

[setEntities:](#) (NSManagedObjectModel)

[setEntities:forConfiguration::](#) (NSManagedObjectModel)

Declared In

NSEntityDescription.h

name

Returns the entity name of the receiver.

```
- (NSString *)name
```

Return Value

The entity name of receiver.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [setName:](#) (page 17)

Related Sample Code

Core Data HTML Store

CoreRecipes

ManagedObjectDataFormatter

Declared In

NSEntityDescription.h

properties

Returns an array containing the properties of the receiver.

```
- (NSArray *)properties
```

Return Value

An array containing the properties of the receiver. The elements in the array are instances of [NSAttributeDescription](#), [NSRelationshipDescription](#), and/or [NSFetchedPropertyDescription](#).

Availability

Available in Mac OS X v10.4 and later.

See Also

- [propertiesByName](#) (page 14)
- [setProperties:](#) (page 17)
- [attributesByName](#) (page 11)
- [relationshipsByName](#) (page 14)

Related Sample Code

ManagedObjectDataFormatter

Declared In

NSEntityDescription.h

propertiesByName

Returns a dictionary containing the properties of the receiver.

- (NSDictionary *)propertiesByName

Return Value

A dictionary containing the receiver's properties, where the keys in the dictionary are the property names and the values are instances of `NSAttributeDescription` and/or `NSRelationshipDescription`.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [attributesByName](#) (page 11)
- [relationshipsByName](#) (page 14)
- [relationshipsWithDestinationEntity:](#) (page 15)

Declared In

NSEntityDescription.h

relationshipsByName

Returns the relationships of the receiver in a dictionary, where the keys in the dictionary are the relationship names.

- (NSDictionary *)relationshipsByName

Return Value

The relationships of the receiver in a dictionary, where the keys in the dictionary are the relationship names and the values are instances of `NSRelationshipDescription`.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [attributesByName](#) (page 11)

- [propertiesByName](#) (page 14)
- [relationshipsWithDestinationEntity:](#) (page 15)

Related Sample Code

Core Data HTML Store
 CoreRecipes
 CustomAtomicStoreSubclass

Declared In

NSEntityDescription.h

relationshipsWithDestinationEntity:

Returns an array containing the relationships of the receiver where the entity description of the relationship is a given entity.

```
- (NSArray *)relationshipsWithDestinationEntity:(NSEntityDescription *)entity
```

Parameters

entity

An entity description.

Return Value

An array containing the relationships of the receiver where the entity description of the relationship is *entity*. Elements in the array are instances of `NSRelationshipDescription`.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [attributesByName](#) (page 11)
- [propertiesByName](#) (page 14)
- [relationshipsByName](#) (page 14)

Declared In

NSEntityDescription.h

renamingIdentifier

Returns the renaming identifier for the receiver.

```
- (NSString *)renamingIdentifier
```

Return Value

The renaming identifier for the receiver.

Discussion

The renaming identifier is used to resolve naming conflicts between models. When creating a mapping model between two managed object models, a source entity and a destination entity that share the same identifier indicate that an entity mapping should be configured to migrate from the source to the destination.

If you do not set this value, the identifier will return the entity's name.

Availability

Available in Mac OS X v10.6 and later.

See Also

- [setRenamingIdentifier:](#) (page 18)

Declared In

NSEntityDescription.h

setAbstract:

Sets whether the receiver represents an abstract entity.

```
- (void)setAbstract:(BOOL)flag
```

Parameters

flag

A Boolean value indicating whether the receiver is abstract (YES) or not (NO).

Special Considerations

This method raises an exception if the receiver's model has been used by an object graph manager.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [isAbstract](#) (page 11)

Declared In

NSEntityDescription.h

setManagedObjectClassName:

Sets the name of the class that represents the receiver's entity.

```
- (void)setManagedObjectClassName:(NSString *)name
```

Parameters

name

The name of the class that represents the receiver's entity.

Discussion

The class specified by *name* must either be, or inherit from, `NSEntityDescription`.

Special Considerations

This method raises an exception if the receiver's model has been used by an object graph manager.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [managedObjectClassName](#) (page 12)

Declared In

NSEntityDescription.h

setName:

Sets the entity name of the receiver.

- (void)setName:(NSString *)*name*

Parameters

name

The name of the entity the receiver describes.

Special Considerations

This method raises an exception if the receiver's model has been used by an object graph manager.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [name](#) (page 13)

Declared In

NSEntityDescription.h

setProperty:

Sets the properties array of the receiver.

- (void)setProperties:(NSArray *)*properties*

Parameters

properties

An array of properties (instances of `NSAttributeDescription`, `NSRelationshipDescription`, and/or `NSFetchedPropertyDescription`).

Special Considerations

This method raises an exception if the receiver's model has been used by an object graph manager.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [properties](#) (page 13)
- [propertiesByName](#) (page 14)
- [attributesByName](#) (page 11)
- [relationshipsByName](#) (page 14)

Declared In

NSEntityDescription.h

setRenamingIdentifier:

Sets the renaming identifier for the receiver.

```
- (void)setRenamingIdentifier:(NSString *)value
```

Parameters

value

The renaming identifier for the receiver.

Availability

Available in Mac OS X v10.6 and later.

See Also

- [renamingIdentifier](#) (page 15)

Declared In

NSEntityDescription.h

setSubentities:

Sets the subentities of the receiver.

```
- (void)setSubentities:(NSArray *)array
```

Parameters

array

An array containing sub-entities for the receiver. Objects in the array must be instances of NSEntityDescription.

Special Considerations

This method raises an exception if the receiver's model has been used by an object graph manager.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [subentities](#) (page 19)

- [subentitiesByName](#) (page 20)

- [superentity](#) (page 20)

Declared In

NSEntityDescription.h

setUserInfo:

Sets the user info dictionary of the receiver.

```
- (void)setUserInfo:(NSDictionary *)dictionary
```

Parameters

dictionary

A user info dictionary.

Special Considerations

This method raises an exception if the receiver's model has been used by an object graph manager.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [userInfo](#) (page 20)

Declared In

NSEntityDescription.h

setVersionHashModifier:

Sets the version hash modifier for the receiver.

```
- (void)setVersionHashModifier:(NSString *)modifierString
```

Parameters

modifierString

The version hash modifier for the receiver.

Discussion

This value is included in the version hash for the entity. You use it to mark or denote an entity as being a different "version" than another even if all of the values which affect persistence are equal. (Such a difference is important in cases where, for example, the structure of an entity is unchanged but the format or content of data has changed.)

Availability

Available in Mac OS X v10.5 and later.

See Also

- [versionHash](#) (page 21)
- [versionHashModifier](#) (page 21)

Declared In

NSEntityDescription.h

subentities

Returns an array containing the sub-entities of the receiver.

```
- (NSArray *)subentities
```

Return Value

An array containing the receiver's sub-entities. The sub-entities are instances of NSEntityDescription.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [setSubentities:](#) (page 18)
- [subentitiesByName](#) (page 20)

- [superentity](#) (page 20)

Declared In

NSEntityDescription.h

subentitiesByName

Returns the sub-entities of the receiver in a dictionary.

- (NSDictionary *)subentitiesByName

Return Value

A dictionary containing the receiver's sub-entities. The keys in the dictionary are the sub-entity names, the corresponding values are instances of NSEntityDescription.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [setSubentities:](#) (page 18)
- [subentities](#) (page 19)
- [superentity](#) (page 20)

Declared In

NSEntityDescription.h

superentity

Returns the super-entity of the receiver.

- (NSEntityDescription *)superentity

Return Value

The receiver's super-entity. If the receiver has no super-entity, returns nil.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [setSubentities:](#) (page 18)
- [subentities](#) (page 19)
- [subentitiesByName](#) (page 20)

Declared In

NSEntityDescription.h

userInfo

Returns the user info dictionary of the receiver.

- (NSDictionary *)userInfo

Return Value

The receiver's user info dictionary.

Availability

Available in Mac OS X v10.4 and later.

See Also

- [setUserInfo:](#) (page 18)

Declared In

NSEntityDescription.h

versionHash

Returns the version hash for the receiver.

```
- (NSData *)versionHash
```

Return Value

The version hash for the receiver.

Discussion

The version hash is used to uniquely identify an entity based on the collection and configuration of properties for the entity. The version hash uses only values which affect the persistence of data and the user-defined [versionHashModifier](#) (page 21) value. (The values which affect persistence are: the name of the entity, the version hash of the superentity (if present), if the entity is abstract, and all of the version hashes for the properties.) This value is stored as part of the version information in the metadata for stores which use this entity, as well as a definition of an entity involved in an `NSEntityMapping` object.

Availability

Available in Mac OS X v10.5 and later.

See Also

- [versionHashModifier](#) (page 21)
- [setVersionHashModifier:](#) (page 19)

Declared In

NSEntityDescription.h

versionHashModifier

Returns the version hash modifier for the receiver.

```
- (NSString *)versionHashModifier
```

Return Value

The version hash modifier for the receiver.

Discussion

This value is included in the version hash for the entity. See [setVersionHashModifier:](#) (page 19) for a full discussion.

Availability

Available in Mac OS X v10.5 and later.

See Also

- [versionHash](#) (page 21)
- [setVersionHashModifier:](#) (page 19)

Declared In

NSEntityDescription.h

Document Revision History

This table describes the changes to *NSEntityDescription Class Reference*.

Date	Notes
2009-05-01	Corrected typographical errors.
2009-02-19	Updated for iPhone OS 3.0.
2008-06-02	Updated for Mac OS X v10.6.
2008-02-08	Updated the discussion of the method <code>insertNewObjectForEntityForName:inManagedObjectContext:</code> for Mac OS X v10.5.
2007-07-23	Updated for Mac OS X v10.5.
2006-05-23	First publication of this content as a separate document.

REVISION HISTORY

Document Revision History

Index

A

attributesByName [instance method 11](#)

C

copy [instance method 11](#)

E

entityForName:inManagedObjectContext: [class method 8](#)

I

insertNewObjectForEntityForName:
inManagedObjectContext: [class method 9](#)
isAbstract [instance method 11](#)
isKindOfEntity: [instance method 12](#)

M

managedObjectClassName [instance method 12](#)
managedObjectModel [instance method 13](#)

N

name [instance method 13](#)

P

properties [instance method 13](#)

propertiesByName [instance method 14](#)

R

relationshipsByName [instance method 14](#)
relationshipsWithDestinationEntity: [instance method 15](#)
renamingIdentifier [instance method 15](#)

S

setAbstract: [instance method 16](#)
setManagedObjectClassName: [instance method 16](#)
setName: [instance method 17](#)
setProperty: [instance method 17](#)
setRenamingIdentifier: [instance method 18](#)
setSubentities: [instance method 18](#)
setUserInfo: [instance method 18](#)
setVersionHashModifier: [instance method 19](#)
subentities [instance method 19](#)
subentitiesByName [instance method 20](#)
superentity [instance method 20](#)

U

userInfo [instance method 20](#)

V

versionHash [instance method 21](#)
versionHashModifier [instance method 21](#)