
NSGetCommand Class Reference

Interapplication Communication



2006-05-23



Apple Inc.
© 2006 Apple Computer, Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Cocoa, Mac, and Mac OS are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY

DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

NSGetCommand Class Reference 5

Overview 5

Document Revision History 7

NSGetCommand Class Reference

Inherits from	NSScriptCommand : NSObject
Conforms to	NSCoding (NSScriptCommand) NSObject (NSObject)
Framework	/System/Library/Frameworks/Foundation.framework
Availability	Available in Mac OS X v10.0 and later.
Declared in	Foundation/NSScriptStandardSuiteCommands.h
Companion guide	Cocoa Scripting Guide

Overview

An instance of `NSGetCommand` gets the specified value or object from the specified scriptable object: for example, the words from a paragraph or the name of a document.

When an instance of `NSGetCommand` is executed, it evaluates the specified receivers, gathers the specified data, if any, and packages it in a return Apple event.

`NSGetCommand` is part of Cocoa's built-in scripting support. It works automatically to support the `get` command through key-value coding. Most applications don't need to subclass `NSGetCommand` or call its methods.

For information on working with `get` commands, see *Getting and Setting Properties and Elements in Cocoa Scripting Guide*.

Document Revision History

This table describes the changes to *NSGetCommand Class Reference*.

Date	Notes
2006-05-23	First publication of this content as a separate document.

REVISION HISTORY

Document Revision History