

---

# CFStringTokenizer Reference

Data Management: Strings, Text, & Fonts



2009-02-03



Apple Inc.  
© 2003, 2009 Apple Inc.  
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.  
1 Infinite Loop  
Cupertino, CA 95014  
408-996-1010

Apple and the Apple logo are trademarks of Apple Inc., registered in the United States and other countries.

iPhone and Numbers are trademarks of Apple Inc.

Simultaneously published in the United States and Canada.

**Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.**

**IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.**

**THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.**

**Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.**

# Contents

---

## **CFStringTokenizer Reference 5**

---

Overview	5
Functions by Task	6
Creating a Tokenizer	6
Setting the String	6
Changing the Location	6
Getting Information About the Current Token	6
Identifying a Language	7
Getting Supported Options for a Language	7
Getting the CFStringTokenizer Type ID	7
Functions	7
CFStringTokenizerAdvanceToNextToken	7
CFStringTokenizerCopyBestStringLanguage	8
CFStringTokenizerCopyCurrentTokenAttribute	8
CFStringTokenizerCreate	9
CFStringTokenizerGetCurrentSubTokens	10
CFStringTokenizerGetCurrentTokenRange	11
CFStringTokenizerGetSupportedOptionsForLanguage	11
CFStringTokenizerGetTypeID	12
CFStringTokenizerGoToTokenAtIndex	12
CFStringTokenizerSetString	13
Data Types	13
CFStringTokenizerRef	13
CFStringTokenizerTokenType	13
Constants	14
Tokenization Modifiers	14
Token Types	15

---

## **Document Revision History 19**

---

## **Index 21**

---



# CFStringTokenizer Reference

---

<b>Derived From:</b>	CType
<b>Framework:</b>	CoreFoundation/CoreFoundation.h
<b>Companion guide</b>	Strings Programming Guide for Core Foundation
<b>Declared in</b>	CFStringTokenizer.h

## Overview

CFStringTokenizer allows you tokenize strings into words, sentences or paragraphs in a language-neutral way. It supports languages such as Japanese and Chinese that do not delimit words by spaces, as well as de-compounding German compounds. You can obtain Latin transcription for tokens. It also provides language identification API.

You can use a CFStringTokenizer to break a string into tokens (sub-strings) on the basis of words, sentences, or paragraphs. When you create a tokenizer, you can supply options to further modify the tokenization — see [Tokenization Modifiers](#) (page 14).

In addition, with CFStringTokenizer:

- You can de-compound German compounds
- You can identify the language used in a string (using [CFStringTokenizerCopyBestStringLanguage](#) (page 8))
- You can obtain Latin transcription for tokens

To find a token that includes the character specified by character index and set it as the current token, you call [CFStringTokenizerGoToTokenAtIndex](#) (page 12). To advance to the next token and set it as the current token, you call [CFStringTokenizerAdvanceToNextToken](#) (page 7). To get the range of current token, you call [CFStringTokenizerGetCurrentTokenRange](#) (page 11). You can use [CFStringTokenizerCopyCurrentTokenAttribute](#) (page 8) to get the attribute of the current token. If the current token is a compound, you can call [CFStringTokenizerGetCurrentSubTokens](#) (page 10) to retrieve the subtokens or derived subtokens contained in the compound token. To guess the language of a string, you call [CFStringTokenizerCopyBestStringLanguage](#) (page 8).

CFStringTokenizer replaces the Language Analysis Manager (see [Language Analysis Manager Reference](#)). The Language Analysis Manager API provides access to one specific language engine at a time. For example you can create an analysis environment for Japanese tokenization, but it can't then be used to tokenize Chinese. Such API is good when you develop a language specific applications that handle a specific language such as input methods. It is not, however, convenient when you develop an internationalized applications which

handle text in language neutral way. Conceptually, `CFStringTokenizer` provides a higher level API that supports typical tasks of internationalized applications. With `CFStringTokenizer` you can tokenize a string without knowing the language.

The following Language Analysis Manager functionality is not available with `CFStringTokenizer`:

- Obtaining the part of speech for a token
- Obtaining alternative tokenization
- Kana-Kanji conversion

## Functions by Task

### Creating a Tokenizer

[CFStringTokenizerCreate](#) (page 9)  
Returns a tokenizer for a given string.

### Setting the String

[CFStringTokenizerSetString](#) (page 13)  
Sets the string for a tokenizer.

### Changing the Location

[CFStringTokenizerAdvanceToNextToken](#) (page 7)  
Advances the tokenizer to the next token and sets that as the current token.

[CFStringTokenizerGoToTokenAtIndex](#) (page 12)  
Finds a token that includes the character at a given index, and set it as the current token.

### Getting Information About the Current Token

[CFStringTokenizerCopyCurrentTokenAttribute](#) (page 8)  
Returns a given attribute of the current token.

[CFStringTokenizerGetCurrentTokenRange](#) (page 11)  
Returns the range of the current token.

[CFStringTokenizerGetCurrentSubTokens](#) (page 10)  
Retrieves the subtokens or derived subtokens contained in the compound token.

## Identifying a Language

[CFStringTokenizerCopyBestStringLanguage](#) (page 8)

Guesses a language of a given string and returns the guess as a BCP 47 string.

## Getting Supported Options for a Language

[CFStringTokenizerGetSupportedOptionsForLanguage](#) (page 11)

Returns supported options for a given language.

## Getting the CFStringTokenizer Type ID

[CFStringTokenizerGetTypeID](#) (page 12)

Returns the type ID for CFStringTokenizer.

# Functions

### CFStringTokenizerAdvanceToNextToken

Advances the tokenizer to the next token and sets that as the current token.

```
CFStringTokenizerTokenType CFStringTokenizerAdvanceToNextToken (
    CFStringTokenizerRef tokenizer
);
```

#### Parameters

*tokenizer*

A CFStringTokenizer object.

#### Return Value

The type of the token if the tokenizer succeeded in finding a token and setting it as current token. Returns `kCFStringTokenizerTokenNone` if the tokenizer failed to find a token. For possible values, see “[Token Types](#)” (page 15).

#### Discussion

If there is no preceding call to [CFStringTokenizerGoToTokenAtIndex](#) (page 12) or [CFStringTokenizerAdvanceToNextToken](#), the function finds the first token in the range specified by the [CFStringTokenizerCreate](#) (page 9). If there is a preceding, successful, call to [CFStringTokenizerGoToTokenAtIndex](#) (page 12) or [CFStringTokenizerAdvanceToNextToken](#) and there is a current token, proceeds to the next token. If a token is found, it is set as the current token and the function returns `true`; otherwise the current token is invalidated and the function returns `false`.

You can obtain the range and attribute of the token calling [CFStringTokenizerGetCurrentTokenRange](#) (page 11) and [CFStringTokenizerCopyCurrentTokenAttribute](#) (page 8). If the token is a compound (with type `kCFStringTokenizerTokenHasSubTokensMask` or `kCFStringTokenizerTokenHasDerivedSubTokensMask`), you can obtain its subtokens and (or) derived subtokens by calling [CFStringTokenizerGetCurrentSubTokens](#) (page 10).

**Availability**

Available in Mac OS X v10.5 and later.

**See Also**

[CFStringTokenizerGoToTokenAtIndex](#) (page 12)

**Declared In**

CFStringTokenizer.h

**CFStringTokenizerCopyBestStringLanguage**

Guesses a language of a given string and returns the guess as a BCP 47 string.

```
CFStringRef CFStringTokenizerCopyBestStringLanguage (
    CFStringRef string,
    CFRange range
);
```

**Parameters**

*string*

The string to test to identify the language.

*range*

The range of *string* to use for the test. If NULL, the first few hundred characters of the string are examined.

**Return Value**

A language in BCP 47 form, or NULL if the language in *string* could not be identified. Ownership follows the Create Rule.

**Discussion**

The result is not guaranteed to be accurate. Typically, the function requires 200-400 characters to reliably guess the language of a string.

CFStringTokenizer recognizes the following languages:

ar (Arabic), bg (Bulgarian), cs (Czech), da (Danish), de (German), el (Greek), en (English), es (Spanish), fi (Finnish), fr (French), he (Hebrew), hr (Croatian), hu (Hungarian), is (Icelandic), it (Italian), ja (Japanese), ko (Korean), nb (Norwegian Bokmål), nl (Dutch), pl (Polish), pt (Portuguese), ro (Romanian), ru (Russian), sk (Slovak), sv (Swedish), th (Thai), tr (Turkish), uk (Ukrainian), zh-Hans (Simplified Chinese), zh-Hant (Traditional Chinese).

**Availability**

Available in Mac OS X v10.5 and later.

**Declared In**

CFStringTokenizer.h

**CFStringTokenizerCopyCurrentTokenAttribute**

Returns a given attribute of the current token.

```

CTypeRef CFStringTokenizerCopyCurrentTokenAttribute (
    CFStringTokenizerRef tokenizer,
    CFOptionFlags attribute
);

```

**Parameters***tokenizer*

A CFStringTokenizer object.

*attribute*

The token attribute to obtain. The value must be `kCFStringTokenizerAttributeLatinTranscription`, or `kCFStringTokenizerAttributeLanguage`.

**Return Value**

The attribute specified by *attribute* of the current token, or NULL if the current token does not have the specified attribute or there is no current token. Ownership follows the Create Rule.

**Availability**

Available in Mac OS X v10.5 and later.

**Declared In**

CFStringTokenizer.h

**CFStringTokenizerCreate**

Returns a tokenizer for a given string.

```

CFStringTokenizerRef CFStringTokenizerCreate (
    CFAllocatorRef alloc,
    CFStringRef string,
    CFRange range,
    CFOptionFlags options,
    CFLocaleRef locale
);

```

**Parameters***alloc*

The allocator to use to allocate memory for the new object. Pass NULL or `kCFAllocatorDefault` to use the current default allocator.

*string*

The string to tokenize.

*range*The range of the characters in *string* to tokenize.*options*

A tokenization unit option that specifies how *string* should be tokenized. The options can be modified by adding unit modifier options to tell the tokenizer to prepare specified attributes when it tokenizes *string*.

For possible values, see [“Tokenization Modifiers”](#) (page 14).

*locale*

A locale that specifies language- or region-specific behavior for the tokenization. You can pass `NULL` to use the default system locale, although this is typically not recommended—instead use `CFLocaleCopyCurrent` to specify the locale of the current user.

For more information, see [“Tokenization Modifiers”](#) (page 14).

**Return Value**

A tokenizer to analyze the range *range* of *string* for the given locale and options. Ownership follows the Create Rule.

**Availability**

Available in Mac OS X v10.5 and later.

**Declared In**

CFStringTokenizer.h

**CFStringTokenizerGetCurrentSubTokens**

Retrieves the subtokens or derived subtokens contained in the compound token.

```
CFIndex CFStringTokenizerGetCurrentSubTokens (
    CFStringTokenizerRef tokenizer,
    CFRange *ranges,
    CFIndex maxRangeLength,
    CFMutableArrayRef derivedSubTokens
);
```

**Parameters***tokenizer*

A `CFStringTokenizer` object.

*tokenizer*

Upon return, an array of `CFRanges` containing the ranges of subtokens. The ranges are relative to the string specified to `CFStringTokenizerCreate`. This parameter can be `NULL`.

*maxRangeLength*

The maximum number of ranges to return.

*derivedSubTokens*

A `CFMutableArray` to which the derived subtokens are to be added. This parameter can be `NULL`.

**Return Value**

The number of ranges returned.

**Discussion**

If token type is `kCFStringTokenizerTokenNone`, the *ranges* array and *derivedSubTokens* array are untouched and the return value is 0.

If token type is `kCFStringTokenizerTokenNormal`, the *ranges* array has one item filled in with the entire range of the token (if *maxRangeLength*  $\geq$  1) and a string taken from the entire token range is added to the *derivedSubTokens* array and the return value is 1.

If token type is `kCFStringTokenizerTokenHasSubTokensMask` or `kCFStringTokenizerTokenHasDerivedSubTokensMask`, the *ranges* array is filled in with as many items as there are subtokens (up to a limit of *maxRangeLength*).

The *derivedSubTokens* array will have sub tokens added even when the sub token is a substring of the token. If token type is `kCFStringTokenizerTokenHasSubTokensMask`, the ordinary non-derived subtokens are added to the *derivedSubTokens* array.

**Availability**

Available in Mac OS X v10.5 and later.

**Declared In**

CFStringTokenizer.h

**CFStringTokenizerGetCurrentTokenRange**

Returns the range of the current token.

```
CFRange CFStringTokenizerGetCurrentTokenRange (
    CFStringTokenizerRef tokenizer
);
```

**Parameters**

*tokenizer*

A CFStringTokenizer object.

**Return Value**

The range of the current token, or `{kCFNotFound, 0}` if there is no current token.

**Availability**

Available in Mac OS X v10.5 and later.

**Declared In**

CFStringTokenizer.h

**CFStringTokenizerGetSupportedOptionsForLanguage**

Returns supported options for a given language.

```
CFOptionFlags CFStringTokenizerGetSupportedOptionsForLanguage (
    CFStringRef language
);
```

**Parameters**

*language*

A BCP 47 language code.

**Return Value**

The options supported for *language*.

**Discussion**

You can use `CFLocaleCopyISOLanguageCodes` to obtain the language code from `CFLocale`.

**Declared In**

CFStringTokenizer.h

## CFStringTokenizerGetTypeID

Returns the type ID for CFStringTokenizer.

```

CTypeID CFStringTokenizerGetTypeID (
    void
);

```

### Return Value

The type ID for CFStringTokenizer.

### Availability

Available in Mac OS X v10.5 and later.

### Declared In

CFStringTokenizer.h

## CFStringTokenizerGoToTokenAtIndex

Finds a token that includes the character at a given index, and set it as the current token.

```

CFStringTokenizerTokenType CFStringTokenizerGoToTokenAtIndex (
    CFStringTokenizerRef tokenizer,
    CFIndex index
);

```

### Parameters

*tokenizer*

A CFStringTokenizer object.

*index*

The index of a character in the string for *tokenizer*.

### Return Value

The type of the token if the tokenizer succeeded in finding a token and setting it as the current token. Returns `kCFStringTokenizerTokenNone` if the tokenizer failed to find a token. For possible values, see “[Token Types](#)” (page 15).

### Discussion

You can obtain the range and attribute of the token calling [CFStringTokenizerGetCurrentTokenRange](#) (page 11) and [CFStringTokenizerCopyCurrentTokenAttribute](#) (page 8). If the token is a compound (with type `kCFStringTokenizerTokenHasSubTokensMask` or `kCFStringTokenizerTokenHasDerivedSubTokensMask`), you can obtain its subtokens and (or) derived subtokens by calling [CFStringTokenizerGetCurrentSubTokens](#) (page 10).

### Availability

Available in Mac OS X v10.5 and later.

### See Also

[CFStringTokenizerAdvanceToNextToken](#) (page 7)

### Declared In

CFStringTokenizer.h

## CFStringTokenizerSetString

Sets the string for a tokenizer.

```
void CFStringTokenizerSetString (
    CFStringTokenizerRef tokenizer,
    CFStringRef string,
    CFRange range
);
```

### Parameters

*tokenizer*

A tokenizer.

*string*

The string for the tokenizer to tokenize.

*range*

The range of string to tokenize. The range of characters within the string to be tokenized. The specified range must not exceed the length of the string.

### Availability

Available in Mac OS X v10.5 and later.

### Declared In

CFStringTokenizer.h

## Data Types

### CFStringTokenizerRef

A reference to a CFStringTokenizer object.

```
typedef struct __CFStringTokenizer * CFStringTokenizerRef;
```

### Availability

Available in Mac OS X v10.5 and later.

### Declared In

CFStringTokenizer.h

### CFStringTokenizerTokenType

Token types returned by [CFStringTokenizerGoToTokenAtIndex](#) (page 12) and [CFStringTokenizerAdvanceToNextToken](#) (page 7).

```
typedef CFOptionFlags CFStringTokenizerTokenType;
```

### Discussion

For possible values, see [Token Types](#) (page 15).

### Availability

Available in Mac OS X v10.5 and later.

**Declared In**

CFStringTokenizer.h

## Constants

### Tokenization Modifiers

Tokenization options are used with [CFStringTokenizerCreate](#) (page 9) to specify how the string should be tokenized

```
enum {
    kCFStringTokenizerUnitWord          = 0,
    kCFStringTokenizerUnitSentence     = 1,
    kCFStringTokenizerUnitParagraph    = 2,
    kCFStringTokenizerUnitLineBreak    = 3,
    kCFStringTokenizerUnitWordBoundary = 4,
    kCFStringTokenizerAttributeLatinTranscription = 1L << 16,
    kCFStringTokenizerAttributeLanguage   = 1L << 17
};
```

**Constants**

kCFStringTokenizerUnitWord

Specifies that a string should be tokenized by word. The *locale* parameter of [CFStringTokenizerCreate](#) (page 9) is ignored.

Available in Mac OS X v10.5 and later.

Declared in CFStringTokenizer.h.

kCFStringTokenizerUnitSentence

Specifies that a string should be tokenized by sentence. The *locale* parameter of [CFStringTokenizerCreate](#) (page 9) is ignored.

Available in Mac OS X v10.5 and later.

Declared in CFStringTokenizer.h.

kCFStringTokenizerUnitParagraph

Specifies that a string should be tokenized by paragraph. The *locale* parameter of [CFStringTokenizerCreate](#) (page 9) is ignored.

Available in Mac OS X v10.5 and later.

Declared in CFStringTokenizer.h.

kCFStringTokenizerUnitLineBreak

Specifies that a string should be tokenized by line break. The *locale* parameter of [CFStringTokenizerCreate](#) (page 9) is ignored.

Available in Mac OS X v10.5 and later.

Declared in CFStringTokenizer.h.

`kCFStringTokenizerUnitWordBoundary`

Specifies that a string should be tokenized by locale-sensitive word boundary.

You can use this constant in double-click range detection and whole word search. It is locale-sensitive. If the locale is `en_US_POSIX`, a colon (U+003A) is treated as a word separator. If the *locale* parameter of `CFStringTokenizerCreate` (page 9) is `NULL`, the locale from the global `AppleTextBreakLocale` preference is used if it is available; otherwise the locale defaults to the first locale in `AppleLanguages`.

`kCFStringTokenizerUnitWordBoundary` also returns space between words as a token.

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

`kCFStringTokenizerAttributeLatinTranscription`

Used with `kCFStringTokenizerUnitWord`, tells the tokenizer to prepare the Latin transcription when it tokenizes the string.

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

`kCFStringTokenizerAttributeLanguage`

Tells the tokenizer to prepare the language (specified as an RFC 3066bis string) when it tokenizes the string.

Used with `kCFStringTokenizerUnitSentence` (page 14) or `kCFStringTokenizerUnitParagraph` (page 14).

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

### Discussion

You use the tokenization unit options with `CFStringTokenizerCreate` (page 9) to specify how a string should be tokenized.

You use the modifiers together with a tokenization unit to modify the way the string is tokenized.

You use the attribute specifiers to tell the tokenizer to prepare the specified attribute when it tokenizes the given string. You can retrieve the attribute value by calling `CFStringTokenizerCopyCurrentTokenAttribute` (page 8) with one of the attribute options.

The locale sensitivity of the tokenization unit options may change in a future release.

### Declared In

`CFStringTokenizer.h`

## Token Types

Token types returned by `CFStringTokenizerGoToTokenAtIndex` (page 12) and `CFStringTokenizerAdvanceToNextToken` (page 7).

```
enum {
    kCFStringTokenizerTokenNone           = 0,
    kCFStringTokenizerTokenNormal        = 1,
    kCFStringTokenizerTokenHasSubTokensMask = 1L << 1,
    kCFStringTokenizerTokenHasDerivedSubTokensMask = 1L << 2,
    kCFStringTokenizerTokenHasNumbersMask = 1L << 3,
    kCFStringTokenizerTokenHasNonLettersMask = 1L << 4,
    kCFStringTokenizerTokenIsCJWordMask  = 1L << 5
};
```

**Constants**

`kCFStringTokenizerTokenNone`

Has no token.

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

`kCFStringTokenizerTokenNormal`

Has a normal token.

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

`kCFStringTokenizerTokenHasSubTokensMask`

Compound token which may contain subtokens but with no derived subtokens.

You can obtain subtokens by calling [CFStringTokenizerGetCurrentSubTokens](#) (page 10).

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

`kCFStringTokenizerTokenHasDerivedSubTokensMask`

Compound token which may contain derived subtokens.

You can obtain subtokens and derived subtokens by calling [CFStringTokenizerGetCurrentSubTokens](#) (page 10).

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

`kCFStringTokenizerTokenHasNumbersMask`

Appears to contain a number.

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

`kCFStringTokenizerTokenHasNonLettersMask`

Contains punctuation, symbols, and so on.

Given the way Unicode word break works, this means it is a standalone punctuation or symbol character, or a string of such.

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

`kCFStringTokenizerTokenIsCJWordMask`

Contains kana and/or ideographs.

Available in Mac OS X v10.5 and later.

Declared in `CFStringTokenizer.h`.

**Discussion**

See [http://www.unicode.org/reports/tr29/#Word\\_Boundaries](http://www.unicode.org/reports/tr29/#Word_Boundaries) for a detailed description of word boundaries.

**Declared In**

CFStringTokenizer.h



# Document Revision History

---

This table describes the changes to *CFStringTokenizer Reference*.

Date	Notes
2009-02-03	Updated for iPhone OS 3.0.
2009-01-06	Added information about the locale sensitivity of each token unit used with the <code>CFStringTokenizerCreate</code> function.
2007-10-31	Added new API.
2007-05-21	New document that describes the opaque typed used to break a string into tokens (sub-strings) on the basis of words, sentences, or paragraphs.

## REVISION HISTORY

### Document Revision History

# Index

---

## C

---

CFStringTokenizerAdvanceToNextToken **function** [7](#)  
CFStringTokenizerCopyBestStringLanguage  
**function** [8](#)  
CFStringTokenizerCopyCurrentTokenAttribute  
**function** [8](#)  
CFStringTokenizerCreate **function** [9](#)  
CFStringTokenizerGetCurrentSubTokens **function**  
[10](#)  
CFStringTokenizerGetCurrentTokenRange **function**  
[11](#)  
CFStringTokenizerGetSupportedOptionsForLanguage  
**function** [11](#)  
CFStringTokenizerGetTypeID **function** [12](#)  
CFStringTokenizerGoToTokenAtIndex **function** [12](#)  
CFStringTokenizerRef **data type** [13](#)  
CFStringTokenizerSetString **function** [13](#)  
CFStringTokenizerTokenType **data type** [13](#)

## K

---

kCFStringTokenizerAttributeLanguage **constant**  
[15](#)  
kCFStringTokenizerAttributeLatinTranscription  
**constant** [15](#)  
kCFStringTokenizerTokenHasDerivedSubTokensMask  
**constant** [16](#)  
kCFStringTokenizerTokenHasNumbersMask  
**constant** [16](#)  
kCFStringTokenizerTokenHasNonLettersMask  
**constant** [16](#)  
kCFStringTokenizerTokenHasSubTokensMask  
**constant** [16](#)  
kCFStringTokenizerTokenIsCJWordMask **constant**  
[16](#)  
kCFStringTokenizerTokenNone **constant** [16](#)  
kCFStringTokenizerTokenNormal **constant** [16](#)  
kCFStringTokenizerUnitLineBreak **constant** [14](#)  
kCFStringTokenizerUnitParagraph **constant** [14](#)

kCFStringTokenizerUnitSentence **constant** [14](#)  
kCFStringTokenizerUnitWord **constant** [14](#)  
kCFStringTokenizerUnitWordBoundary **constant** [15](#)

## T

---

Token Types [15](#)  
Tokenization Modifiers [14](#)