
CAOpenGLLayer Class Reference

Graphics & Animation: Animation



2008-03-11



Apple Inc.
© 2008 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Mac, Mac OS, Objective-C, and Quartz are trademarks of Apple Inc., registered in the United States and other countries.

OpenGL is a registered trademark of Silicon Graphics, Inc.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

CAOpenGLLayer Class Reference 5

Overview 5

Tasks 5

 Drawing the Content 5

 Managing the Pixel Format 6

 Managing the Rendering Context 6

Properties 6

 asynchronous 6

Instance Methods 7

 canDrawInCGLContext:pixelFormat:forLayerTime:displayTime: 7

 copyCGLContextForPixelFormat: 7

 copyCGLPixelFormatForDisplayMask: 8

 drawInCGLContext:pixelFormat:forLayerTime:displayTime: 8

 isAsynchronous 9

 releaseCGLContext: 9

 releaseCGLPixelFormat: 9

Document Revision History 11

Index 13

CAOpenGLLayer Class Reference

Inherits from	CALayer : NSObject
Conforms to	NSCoding (CALayer) CAMediaTiming (CALayer) NSObject (NSObject)
Framework	/System/Library/Frameworks/QuartzCore.framework
Availability	Available in Mac OS X v10.5 and later.
Declared in	CAOpenGLLayer.h
Companion guides	Core Animation Programming Guide Core Animation Cookbook
Related sample code	CALayerEssentials

Overview

`CAOpenGLLayer` provides a layer suitable for rendering OpenGL content.

To provide OpenGL content you subclass `CAOpenGLLayer` and override `drawInCGLContext:pixelFormat:forLayerTime:displayTime:` (page 8). You can specify that the OpenGL content is static by setting the `asynchronous` (page 6) property to `NO`.

Tasks

Drawing the Content

- `asynchronous` (page 6) *property*
Determines when the contents of the layer are updated.
- `isAsynchronous` (page 9)
A synthesized accessor for the `asynchronous` (page 6) property.
- `canDrawInCGLContext:pixelFormat:forLayerTime:displayTime:` (page 7)
Returns whether the receiver should draw OpenGL content for the specified time.
- `drawInCGLContext:pixelFormat:forLayerTime:displayTime:` (page 8)
Draws the OpenGL content for the specified time.

Managing the Pixel Format

- [copyCGLPixelFormatForDisplayMask:](#) (page 8)
Returns the OpenGL pixel format suitable for rendering to the set of displays specified by the display mask.
- [releaseCGLPixelFormat:](#) (page 9)
Releases the specified OpenGL pixel format object.

Managing the Rendering Context

- [copyCGLContextForPixelFormat:](#) (page 7)
Returns the rendering context the receiver requires for the specified pixel format.
- [releaseCGLContext:](#) (page 9)
Releases the specified rendering context.

Properties

For more about Objective-C properties, see “Properties” in *The Objective-C Programming Language*.

asynchronous

Determines when the contents of the layer are updated.

@property BOOL asynchronous

Discussion

If NO, the contents of the layer are updated only in response to receiving a `setNeedsDisplay` message. When YES, the receiver’s `canDrawInCGLContext:pixelFormat:forLayerTime:displayTime:` (page 7) is called periodically to determine if the OpenGL content should be updated.

Availability

Available in Mac OS X v10.5 and later.

See Also

- [isAsynchronous](#) (page 9)

Related Sample Code

CALayerEssentials

Declared In

CAOpenGLLayer.h

Instance Methods

canDrawInCGLContext:pixelFormat:forLayerTime:displayTime:

Returns whether the receiver should draw OpenGL content for the specified time.

```
- (BOOL)canDrawInCGLContext:(CGLContextObj)glContext
  pixelFormat:(CGLPixelFormatObj)pixelFormat
  forLayerTime:(CFTimeInterval)timeInterval
  displayTime:(const CVTimeStamp *)timeStamp
```

Parameters

glContext

The CGLContextObj in to which the OpenGL content would be drawn.

pixelFormat

The pixel format used when the *glContext* was created.

timeInterval

The current layer time.

timeStamp

The display timestamp associated with *timeInterval*. Can be null.

Return Value

YES if the receiver should render OpenGL content, NO otherwise.

Discussion

This method is called before attempting to render the frame for the layer time specified by *timeInterval*. If the method returns NO, the frame is skipped. The default implementation always returns YES.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CAOpenGLLayer.h

copyCGLContextForPixelFormat:

Returns the rendering context the receiver requires for the specified pixel format.

```
- (CGLContextObj)copyCGLContextForPixelFormat:(CGLPixelFormatObj)pixelFormat
```

Parameters

pixelFormat

The pixel format for the rendering context.

Return Value

A new CGLContext with renderers for *pixelFormat*.

Discussion

This method is called when a rendering context is needed by the receiver. The default implementation allocates a new context with a null share context.

You should not call this method directly, it is intended to be overridden by subclasses.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CAOpenGLLayer.h

copyCGLPixelFormatForDisplayMask:

Returns the OpenGL pixel format suitable for rendering to the set of displays specified by the display mask.

```
- (CGLPixelFormatObj)copyCGLPixelFormatForDisplayMask:(uint32_t)mask
```

Parameters

mask

The display mask the OpenGL content will be rendered on.

Discussion

This method is called when a pixel format object is needed for the receiver. The default implementation returns a 32bpp fixed point pixel format, with the `NoRecovery` and `Accelerated` flags set.

You should not call this method directly, it is intended to be overridden by subclasses.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CAOpenGLLayer.h

drawInCGLContext:pixelFormat:forLayerTime:displayTime:

Draws the OpenGL content for the specified time.

```
- (void)drawInCGLContext:(CGLContextObj)glContext
    pixelFormat:(CGLPixelFormatObj)pixelFormat
    forLayerTime:(CFTimeInterval)timeInterval
    displayTime:(const CVTimeStamp *)timeStamp
```

Parameters

glContext

The rendering context in to which the OpenGL content should be rendered.

pixelFormat

The pixel format used when the *glContext* was created.

timeInterval

The current layer time.

timeStamp

The display timestamp associated with *timeInterval*. Can be null.

Discussion

This method is called when a new frame needs to be generated for the layer time specified by *timeInterval*. The viewport of *glContext* is set correctly for the size of the layer. No other state is defined. If the method enables OpenGL features, it should disable them before returning.

The default implementation of the method flushes the context.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CAOpenGLLayer.h

isAsynchronous

A synthesized accessor for the [asynchronous](#) (page 6) property.

- (BOOL)isAsynchronous

See Also

[@property asynchronous](#) (page 6)

releaseCGLContext:

Releases the specified rendering context.

- (void)releaseCGLContext:(CGLContextObj)*glContext*

Parameters

glContext

The rendering context to release.

Discussion

This method is called when the OpenGL context that was previously returned by [copyCGLContextForPixelFormat:](#) (page 7) is no longer needed.

You should not call this method directly, it is intended to be overridden by subclasses.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CAOpenGLLayer.h

releaseCGLPixelFormat:

Releases the specified OpenGL pixel format object.

- (void)releaseCGLPixelFormat:(CGLPixelFormatObj)*pixelFormat*

Parameters

pixelFormat

The pixel format object to release.

Discussion

This method is called when the OpenGL pixel format that was previously returned by [copyCGLContextForPixelFormat:](#) (page 7).

You should not call this method directly, it is intended to be overridden by subclasses.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CAOpenGLLayer.h

Document Revision History

This table describes the changes to *CAOpenGLLayer Class Reference*.

Date	Notes
2008-03-11	Clarified that <code>copyCGLPixelFormatForDisplayMask</code> , <code>copyCGLContextForPixelFormat</code> , <code>releaseCGLContext</code> , and <code>releaseCGLPixelFormat</code> should only be implemented, never called.
2007-07-24	New document that describes the class that provides a context for rendering OpenGL in a layer.

REVISION HISTORY

Document Revision History

Index

A

asynchronous [instance property 6](#)

C

canDrawInCGLContext:pixelFormat:forLayerTime:
displayTime: [instance method 7](#)

copyCGLContextForPixelFormat: [instance method 7](#)

copyCGLPixelFormatForDisplayMask: [instance method 8](#)

D

drawInCGLContext:pixelFormat:forLayerTime:
displayTime: [instance method 8](#)

I

isAsynchronous [instance method 9](#)

R

releaseCGLContext: [instance method 9](#)

releaseCGLPixelFormat: [instance method 9](#)