
IKSlideshow Class Reference

Graphics & Animation: 2D Drawing



2009-06-02



Apple Inc.
© 2009 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, iPhoto, Mac, Mac OS, Objective-C, and Quartz are trademarks of Apple Inc., registered in the United States and other countries.

Aperture is a trademark of Apple Inc.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

IKSlideshow Class Reference 5

Overview 5

Tasks 5

 Creating a Shared Instance of a Slideshow 5

 Running and Stopping a Slideshow 5

 Getting Slideshow Data 6

 Reloading Data 6

 Exporting Slideshow Items 6

Properties 6

 autoPlayDelay 6

Class Methods 6

 canExportToApplication: 6

 exportSlideshowItem:toApplication: 7

 sharedSlideshow 7

Instance Methods 8

 indexOfCurrentSlideshowItem 8

 reloadData 8

 reloadSlideshowItemAtIndex: 8

 runSlideshowWithDataSource:inMode:options: 9

 stopSlideshow: 9

Constants 10

 Bundle Identifiers 10

 Slideshow Modes 10

 Slideshow Option Keys 11

Document Revision History 13

Index 15

IKSlideshow Class Reference

Inherits from	NSObject
Conforms to	NSObject (NSObject)
Framework	System/Library/Frameworks/Quartz.framework/ImageKit.framework
Availability	Available in Mac OS X v10.5 and later.
Declared in	IKSlideshow.h
Related sample code	ImageKitDemo

Overview

The `IKSlideshow` class encapsulates a data source and options for a slideshow.

Tasks

Creating a Shared Instance of a Slideshow

- + `sharedSlideshow` (page 7)
Returns a shared instance of a slideshow.

Running and Stopping a Slideshow

- `runSlideshowWithDataSource:inMode:options:` (page 9)
Runs a slideshow that contains the specified kind of items, provided from a data source.
- `stopSlideshow:` (page 9)
Stops a slideshow.
- `autoplayDelay` (page 6) *property*
Controls the interval of time before a slideshow starts to play automatically.

Getting Slideshow Data

- [indexOfCurrentSlideshowItem](#) (page 8)
Returns the index of the current slideshow item.

Reloading Data

- [reloadData](#) (page 8)
Reloads the data for a slideshow.
- [reloadSlideshowItemAtIndex:](#) (page 8)
Reloads the data for a slideshow, starting at the specified index.

Exporting Slideshow Items

- + [canExportToApplication:](#) (page 6)
Finds out whether the slideshow can export its contents to an application.
- + [exportSlideshowItem:toApplication:](#) (page 7)
Exports a slideshow item to the application that has the provided bundle identifier.

Properties

For more about Objective-C properties, see “Properties” in *The Objective-C Programming Language*.

autoplayDelay

Controls the interval of time before a slideshow starts to play automatically.

```
@property NSTimeInterval autoplayDelay
```

Availability

Available in Mac OS X v10.5 and later.

Declared In

IKSlideshow.h

Class Methods

canExportToApplication:

Finds out whether the slideshow can export its contents to an application.

```
+ (BOOL)canExportToApplication:(NSString *)applicationBundleIdentifier
```

Parameters

applicationBundleIdentifier

The bundle identifier of the application that you want to export the slideshow to. See “[Bundle Identifiers](#)” (page 10).

Return Value

YES if the slideshow can be exported to the specified application; NO otherwise.

Availability

Available in Mac OS X v10.5 and later.

See Also

+ [exportSlideshowItem:toApplication:](#) (page 7)

Declared In

IKSlideshow.h

exportSlideshowItem:toApplication:

Exports a slideshow item to the application that has the provided bundle identifier.

```
+ (void)exportSlideshowItem:(id)item toApplication:(NSString  
*)applicationBundleIdentifier
```

Parameters

item

The item to export

applicationBundleIdentifier

The bundle identifier of the application that you want to export the item to.

Availability

Available in Mac OS X v10.5 and later.

See Also

+ [canExportToApplication:](#) (page 6)

Declared In

IKSlideshow.h

sharedSlideshow

Returns a shared instance of a slideshow.

```
+ (IKSlideshow *)sharedSlideshow
```

Return Value

A slideshow object.

Availability

Available in Mac OS X v10.5 and later.

Related Sample Code

ImageKitDemo

Declared In
IKSlideshow.h

Instance Methods

indexOfCurrentSlideshowItem

Returns the index of the current slideshow item.

- (NSInteger)indexOfCurrentSlideshowItem

Return Value

The index of the current item in the slideshow.

Availability

Available in Mac OS X v10.5 and later.

Related Sample Code

ImageKitDemo

Declared In

IKSlideshow.h

reloadData

Reloads the data for a slideshow.

- (void)reloadData

Availability

Available in Mac OS X v10.5 and later.

See Also

- [reloadSlideshowItemAtIndex:](#) (page 8)

Declared In

IKSlideshow.h

reloadSlideshowItemAtIndex:

Reloads the data for a slideshow, starting at the specified index.

- (void)reloadSlideshowItemAtIndex:(NSInteger) *index*

Parameters

index

The index that species where to reload the slideshow data.

Availability

Available in Mac OS X v10.5 and later.

See Also

- [reloadData](#) (page 8)

Declared In

IKSlideshow.h

runSlideshowWithDataSource:inMode:options:

Runs a slideshow that contains the specified kind of items, provided from a data source.

```
- (void)runSlideshowWithDataSource:(id < IKSlideshowDataSource >)dataSource
    inMode:(NSString *)slideshowMode options:(NSDictionary *)slideshowOptions
```

Parameters

dataSource

The data source to use for the slideshow.

slideshowMode

A constant that indicate what kind of items are in the slideshow—`IKSlideshowModeImages`, `IKSlideshowModePDF`, or `IKSlideshowModeQuickLook`. See “[Slideshow Modes](#)” (page 10).

slideshowOptions

A dictionary of slideshow options. See “[Slideshow Option Keys](#)” (page 11).

Availability

Available in Mac OS X v10.5 and later.

See Also

- [stopSlideshow:](#) (page 9)

Related Sample Code

ImageKitDemo

Declared In

IKSlideshow.h

stopSlideshow:

Stops a slideshow.

```
- (void)stopSlideshow:(id)sender
```

Parameters

sender

The object sending the message to stop the slideshow.

Discussion

This method is invoked when the user clicks a button or issues a stop command.

Availability

Available in Mac OS X v10.5 and later.

See Also

- [runSlideshowWithDataSource:inMode:options:](#) (page 9)

Declared In

IKSlideshow.h

Constants

Bundle Identifiers

Identifiers for exporting slideshow items to an application.

```
NSString *const IK_iPhotoBundleIdentifier;
NSString *const IK_AperatureBundleIdentifier;
NSString *const IK_MailBundleIdentifier;
```

Constants

`IK_iPhotoBundleIdentifier`
The iPhoto application—com.apple.iPhoto.
 Available in Mac OS X v10.5 and later.
 Declared in `IKSlideshow.h`.

`IK_AperatureBundleIdentifier`
The Aperature application—com.apple.Aperature.
 Available in Mac OS X v10.6 and later.
 Declared in `IKSlideshow.h`.

`IK_MailBundleIdentifier`
The Mail application—com.apple.mail.
 Available in Mac OS X v10.6 and later.
 Declared in `IKSlideshow.h`.

Slideshow Modes

The kind of items in the slideshow.

```
NSString *const IKSlideshowModeImages;
NSString *const IKSlideshowModePDF;
NSString *const IKSlideshowModeOther;
```

Constants

`IKSlideshowModeImages`
All items in the slideshow are images.
 Available in Mac OS X v10.5 and later.
 Declared in `IKSlideshow.h`.

`IKSlideshowModePDF`
All items in the slideshow are PDF documents.
 Available in Mac OS X v10.5 and later.
 Declared in `IKSlideshow.h`.

IKSlideshowModeOther

There are a mixture of items in the slideshow (image, PDF, text, HTML, and so on).

Available in Mac OS X v10.5 and later.

Declared in `IKSlideshow.h`.

Slideshow Option Keys

Keys for slideshow options.

```
NSString *const IKSlideshowWrapAround;
NSString *const IKSlideshowStartPaused;
NSString *const IKSlideshowStartIndex;
NSString *const IKSlideshowPDFDisplayBox;
NSString *const IKSlideshowPDFDisplayMode;
NSString *const IKSlideshowPDFDisplaysAsBook;
NSString *const IKSlideshowScreen;
NSString *const IKSlideshowAudioFile;
```

Constants

IKSlideshowWrapAround

A key for starting the slideshow over after the last slide shows. The associated value is a `Boolean` data type.

Available in Mac OS X v10.5 and later.

Declared in `IKSlideshow.h`.

IKSlideshowStartPaused

A key for starting in a paused state. The associated value is a `Boolean` data type.

Available in Mac OS X v10.5 and later.

Declared in `IKSlideshow.h`.

IKSlideshowStartIndex

A key for the slideshow item index. The associated value is an index.

Available in Mac OS X v10.5 and later.

Declared in `IKSlideshow.h`.

IKSlideshowPDFDisplayBox

A key for the PDF display box. The associated value is a type of display box, such as `kPDFDisplayBoxMediaBox` or `kPDFDisplayBoxMediaBox`. See *PDFPage Class Reference* for more information.

Available in Mac OS X v10.5 and later.

Declared in `IKSlideshow.h`.

IKSlideshowPDFDisplayMode

A key for the PDF display mode. The associated value is a PDF display mode constant, such as `kPDFDisplaySinglePage` or `kPDFDisplayTwoUp`. See *PDFView Class Reference* for more information.

Available in Mac OS X v10.5 and later.

Declared in `IKSlideshow.h`.

IKSlideshowPDFDisplaysAsBook

A key for displaying the slideshow as a book. The associated value is a `Boolean` data type.

Available in Mac OS X v10.5 and later.

Declared in `IKSlideshow.h`.

IKSlideshowScreen

A key specifying the screen on which the slideshow is displayed. The associated value is an `NSScreen` object. By default `mainScreen` is used.

Available in Mac OS X v10.6 and later.

Declared in `IKSlideshow.h`.

IKSlideshowAudioFile

A key specifying the audio file played during the slideshow. The associated value is an `NSURL` object.

Available in Mac OS X v10.6 and later.

Declared in `IKSlideshow.h`.

Document Revision History

This table describes the changes to *IKSlideshow Class Reference*.

Date	Notes
2009-06-02	Updated for Mac OS X v10.6. New constants for screen and audio playback.
2007-10-31	New document that describes the class that encapsulates a data source and options for a slideshow.

REVISION HISTORY

Document Revision History

Index

A

autoplayDelay **instance property** [6](#)

B

Bundle Identifiers [10](#)

C

canExportToApplication: **class method** [6](#)

E

exportSlideshowItem:toApplication: **class method** [7](#)

I

IKSlideshowAudioFile **constant** [12](#)
IKSlideshowModeImages **constant** [10](#)
IKSlideshowModeOther **constant** [11](#)
IKSlideshowModePDF **constant** [10](#)
IKSlideshowPDFDisplayBox **constant** [11](#)
IKSlideshowPDFDisplayMode **constant** [11](#)
IKSlideshowPDFDisplaysAsBook **constant** [11](#)
IKSlideshowScreen **constant** [12](#)
IKSlideshowStartIndex **constant** [11](#)
IKSlideshowStartPaused **constant** [11](#)
IKSlideshowWrapAround **constant** [11](#)
IK_ApertureBundleIdentifier **constant** [10](#)
IK_iPhotoBundleIdentifier **constant** [10](#)
IK_MailBundleIdentifier **constant** [10](#)
indexOfCurrentSlideshowItem **instance method** [8](#)

R

reloadData **instance method** [8](#)
reloadSlideshowItemAtIndex: **instance method** [8](#)
runSlideshowWithDataSource:inMode:options:
 instance method [9](#)

S

sharedSlideshow **class method** [7](#)
Slideshow Modes [10](#)
Slideshow Option Keys [11](#)
stopSlideshow: **instance method** [9](#)