
ABAddressBook C Reference

Data Management: Contact Data



2007-07-08



Apple Inc.
© 2002, 2007 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Carbon, Mac, Mac OS, and Objective-C are trademarks of Apple Inc., registered in the United States and other countries.

Java and all Java-based trademarks are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS

PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

ABAddressBook C Reference 5

Overview	5
Functions	6
ABAddPropertiesAndTypes	6
ABAddRecord	6
ABCopyArrayOfAllGroups	7
ABCopyArrayOfAllPeople	7
ABCopyArrayOfMatchingRecords	8
ABCopyArrayOfPropertiesForRecordType	8
ABCopyDefaultCountryCode	9
ABCopyRecordForUniqueld	9
ABCopyRecordTypeFromUniqueld	9
ABCreateFormattedAddressFromDictionary	10
ABGetMe	10
ABGetSharedAddressBook	11
ABHasUnsavedChanges	11
ABRemoveProperties	12
ABRemoveRecord	12
ABSave	13
ABSetMe	13
ABTypeOfProperty	14
Data Types	14
ABAddressBookRef	14
Constants	14
Property Types	14
Database Notifications	16

Document Revision History 19

Index 21

ABAddressBook C Reference

Derived From:	CType
Framework:	AddressBook/ABAddressBookC.h
Companion guide	Address Book Programming Guide for Mac OS X
Declared in	ABAddressBookC.h ABGlobals.h ABTypeDefs.h

Overview

The `ABAddressBook` opaque type provides a programming interface to the Address Book—a centralized database used by multiple applications to store contact and other personal information about people. The Address Book database also supports the notion of a “group” containing one or more persons. People may belong to multiple groups, and groups may also belong to other groups.

The `ABAddressBook` opaque type provides functions for accessing, adding, and removing group and person records including the “me” record corresponding to the logged-in user. For example, you use the [ABCopyArrayOfAllGroups](#) (page 7) function to get an array of all the group records in the database, or the [ABCopyArrayOfAllPeople](#) (page 7) function to get all the person records. You use the [ABGetMe](#) (page 10) function to get the person record corresponding to the logged-in user. You can also add and remove records using the [ABAddRecord](#) (page 6) and [ABRemoveRecord](#) (page 12) functions.

You can also search for records matching a particular query you specify by creating an `ABSearchElement` object. You use the `ABGroupCreateSearchElement` or `ABPersonCreateSearchElement` function to create an `ABSearchElement` object for the corresponding record. Then use the [ABCopyArrayOfMatchingValues](#) (page 8) `ABAddressBook` function, passing the `ABSearchElement` as the argument, to query the database. See `ABSearchElement` for more functions that create compound queries.

Your application uses a shared instance of `ABAddressBook` returned by the [ABGetSharedAddressBook](#) (page 11) function to interact with the database (multiple `ABAddressBook` instances are not supported). Changes you make to the record objects are stored in memory, and saved to disk when you invoke the [ABSave](#) (page 13) function.

The Address Book posts notifications if any application including yours makes changes to the database. Typically, you observe these notifications to update any dependent view or model objects in your application. Use `CFNotificationCenter` to register for the `ABAddressBook` notifications: [kABDatabaseChangedNotification](#) (page 17) and [kABDatabaseChangedExternallyNotification](#) (page 17). These notifications are not sent until [ABGetSharedAddressBook](#) (page 11) is called.

The `ABAddressBook` opaque type is “toll-free bridged” with its Objective-C counterpart. This means that the `ABAddressBookRef` type is interchangeable in function or method calls with instances of the `ABAddressBook` class.

Functions

ABAddPropertiesAndTypes

Adds the given properties to all the records of the specified type in the Address Book database, and returns the number of properties successfully added.

```
CFIndex ABAddPropertiesAndTypes (
    ABAddressBookRef addressBook,
    CFStringRef recordType,
    CFDictionaryRef propertiesAndTypes
);
```

Parameters

addressBook

The address book for the logged-in user.

recordType

The record type you wish to add properties to: `kABGroupRecordType` or `kABPersonRecordType`.

propertiesAndTypes

A `CFDictionary` object containing the properties to add. In each dictionary entry, the key is a string with the property’s name, and the value is a constant with the property’s type. The property’s name must be unique. You may want to use Java-style package names for your properties, for example, “org.dogclub.dogname” or “com.mycompany.customerID”. The property type must be one of the constants described in [Property Types](#) (page 14).

Return Value

The number of properties successfully added.

Availability

Available in Mac OS X v10.2 and later.

Declared In

`ABAddressBookC.h`

ABAddRecord

Adds a record of the specified type to the Address Book database.

```
bool ABAddRecord (
    ABAddressBookRef addressBook,
    ABRecordRef record
);
```

Parameters

addressBook

The address book for the logged-in user.

record

The record to add to the Address Book database. If this parameter is `NULL`, the function raises an exception.

Return Value

`true` if the record was added successfully, `false` otherwise.

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

ABCopyArrayOfAllGroups

Returns an array of all the groups in the Address Book database.

```
CFArrayRef ABCopyArrayOfAllGroups (
    ABAddressBookRef addressBook
);
```

Parameters

addressBook

The address book for the logged-in user.

Return Value

An array of `ABGroup` objects representing all the groups in the Address Book database. If the database doesn't contain any groups, the function returns an empty array. You are responsible for releasing this object.

Availability

Available in Mac OS X v10.3 and later.

Declared In

ABAddressBookC.h

ABCopyArrayOfAllPeople

Returns an array of all the people in the Address Book database.

```
CFArrayRef ABCopyArrayOfAllPeople (
    ABAddressBookRef addressBook
);
```

Parameters

addressBook

The address book for the logged-in user.

Return Value

An array of `ABPerson` objects representing all the people in the Address Book database. If the database does not contain any people, the function returns an empty array. You are responsible for releasing this object.

Availability

Available in Mac OS X v10.3 and later.

Declared In

ABAddressBookC.h

ABCopyArrayOfMatchingRecords

Returns an array of records that match the given search element, or an empty array if no records match the search element.

```
CFArrayRef ABCopyArrayOfMatchingRecords (
    ABAddressBookRef addressBook,
    ABSearchElementRef search
);
```

Parameters*addressBook*

The address book for the logged-in user.

search

The search element that specifies the query. If *search* is NULL, this function raises an exception.

Create an ABSearchElement object using the record specific functions:

ABGroupCreateSearchElement or ABPersonCreateSearchElement. See ABSearchElement for more functions that create compound queries.

Return Value

A new array containing ABRecord objects representing all the records that match *search*. If no records match *search*, this function returns an empty array. You are responsible for releasing this object.

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

ABCopyArrayOfPropertiesForRecordType

Returns an array containing the names of all the properties for the specified record type.

```
CFArrayRef ABCopyArrayOfPropertiesForRecordType (
    ABAddressBookRef addressBook,
    CFStringRef recordType
);
```

Parameters*addressBook*

The address book for the logged-in user.

recordType

Specifies the type of record: kABGroupRecordType or kABPersonRecordType.

Return Value

An new array containing the names (CFString objects) of all the properties in *recordType*. You are responsible for releasing this object.

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

ABCopyDefaultCountryCode

Returns the default country code for records with unspecified country codes.

```
CFStringRef ABCopyDefaultCountryCode (
    ABAddressBookRef addressBook
);
```

Parameters*addressBook*

The address book for the logged-in user.

Return Value

A string with the default country code. You are responsible for releasing this object.

Availability

Available in Mac OS X v10.3 and later.

Declared In

ABAddressBookC.h

ABCopyRecordForUniqueId

Returns the record that matches the given unique ID.

```
ABRecordRef ABCopyRecordForUniqueId (
    ABAddressBookRef addressBook,
    CFStringRef uniqueId
);
```

Parameters*addressBook*

The address book for the logged-in user.

*uniqueId*A unique ID for the record. If this is `NULL`, this function raises an exception.**Return Value**The record that matches the given unique ID. If no record matches *uniqueId*, the function returns `NULL`. You are responsible for releasing this object.**Availability**

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

ABCopyRecordTypeFromUniqueId

Returns the type name of the record that matches a given unique ID.

```

CFStringRef ABCopyRecordTypeFromUniqueId (
    ABAddressBookRef addressBook,
    CFStringRef uniqueId
);

```

Parameters

addressBook

The address book for the logged-in user.

uniqueId

A unique ID for the record. If this is NULL, this function raises an exception.

Return Value

A string with the name of the type for the record that matches the given unique ID. You are responsible for releasing this object.

Availability

Available in Mac OS X v10.3 and later.

Declared In

ABAddressBookC.h

ABCreateFormattedAddressFromDictionary

Returns a string containing the formatted address.

```

CFStringRef ABCreateFormattedAddressFromDictionary (
    ABAddressBookRef addressBook,
    CFDictionaryRef address
);

```

Parameters

addressBook

The address book for the logged-in user.

Return Value

Returns a string containing the formatted address. You are responsible for releasing this object.

Availability

Available in Mac OS X v10.3 and later.

Declared In

ABAddressBookC.h

ABGetMe

Returns the ABPerson object for the logged-in user.

```

ABPersonRef ABGetMe (
    ABAddressBookRef addressBook
);

```

Parameters

addressBook

The address book for the logged-in user.

Return Value

The ABPerson record that represents the logged-in user, or NULL if the user never specified such a record. You are responsible for retaining and releasing this object as needed.

Availability

Available in Mac OS X v10.2 and later.

Related Sample Code

MyFirstJNIProject

Declared In

ABAddressBookC.h

ABGetSharedAddressBook

Returns the unique shared ABAddressBook object.

```
ABAddressBookRef ABGetSharedAddressBook (
    void
);
```

Return Value

The address book for the logged-in user. You are responsible for retaining and releasing this object as needed.

Discussion

Every application shares the address book for the logged-in user and this function returns it. If you call this function more than once or try to create a new address book, you get a pointer to the same shared address book.

Availability

Available in Mac OS X v10.2 and later.

Related Sample Code

MyFirstJNIProject

Declared In

ABAddressBookC.h

ABHasUnsavedChanges

Returns whether if there are unsaved changes in the address book.

```
bool ABHasUnsavedChanges (
    ABAddressBookRef addressBook
);
```

Parameters

addressBook

The address book for the logged-in user.

Return Value

true if there are unsaved changes, false otherwise.

Discussion

The unsaved changes flag is set automatically whenever changes are made to the address book.

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

ABRemoveProperties

Removes the given properties from all the records of this type in the Address Book database, and returns the number of properties successfully removed.

```
CFIndex ABRemoveProperties (
    ABAddressBookRef addressBook,
    CFStringRef recordType,
    CFArrayRef properties
);
```

Parameters

addressBook

The address book for the logged-in user.

recordType

The name of record to remove the properties from: `kABGroupRecordType` or `kABPersonRecordType`.

properties

An array of properties (CFString objects) to remove.

Return Value

The number of properties successfully removed.

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

ABRemoveRecord

Removes the specified record from the Address Book database.

```
bool ABRemoveRecord (
    ABAddressBookRef addressBook,
    ABRecordRef record
);
```

Parameters

addressBook

The address book for the logged-in user.

record

The ABRecord object to be removed. If `NULL`, this function raises an exception.

Return Value

true if the record was removed successfully, false otherwise.

Availability

Available in Mac OS X 10.2 and later.

Declared In

ABAddressBookC.h

ABSave

Saves all the changes made since the last save.

```
bool ABSave (
    ABAddressBookRef addressBook
);
```

Parameters

addressBook

The address book for the logged-in user.

Return Value

true if this function is successful or if there were no changes, false otherwise.

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

ABSetMe

Sets the record that represents the logged-in user.

```
void ABSetMe (
    ABAddressBookRef addressBook,
    ABPersonRef moi
);
```

Parameters

addressBook

The address book for the logged-in user.

person

The ABPerson object that represents the logged-in user. Pass NULL if you don't want a record to represent the logged-in user.

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

ABTypeOfProperty

Returns the type of a given property for a given record.

```
ABPropertyType ABTypeOfProperty (
    ABAddressBookRef addressBook,
    CFStringRef recordType,
    CFStringRef property
);
```

Parameters

addressBook

The address book for the logged-in user.

recordType

The record type that contains *property*: `kABGroupRecordType` or `kABPersonRecordType`.

property

The property whose type you wish to obtain.

Return Value

The type of *property* as defined in [Property Types](#) (page 14). If *property* does not exist in *recordType*, this function returns `kABErrorInProperty`.

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

Data Types

ABAddressBookRef

A reference to an `ABAddressBook` object.

```
typedef struct __ABAddressBookRef *ABAddressBookRef;
```

Availability

Available in Mac OS X v10.2 and later.

Declared In

ABAddressBookC.h

Constants

Property Types

These are the possible types of `ABRecord` properties.

```
typedef enum _ABPropertyType {
    kABErrorInProperty = 0x0,
    kABStringProperty = 0x1,
    kABIntegerProperty = 0x2,
    kABRealProperty = 0x3,
    kABDateProperty = 0x4,
    kABArrayProperty = 0x5,
    kABDictionaryProperty = 0x6,
    kABDataProperty = 0x7,
    kABMultiStringProperty = 0x100 | kABStringProperty,
    kABMultiIntegerProperty = 0x100 | kABIntegerProperty,
    kABMultiRealProperty = 0x100 | kABRealProperty,
    kABMultiDateProperty = 0x100 | kABDateProperty,
    kABMultiArrayProperty = 0x100 | kABArrayProperty,
    kABMultiDictionaryProperty = 0x100 | kABDictionaryProperty,
    kABMultiDataProperty = 0x100 | kABDataProperty
} ABPropertyType;
```

Constants

kABErrorInProperty

Returned by some functions when an invalid property is used.

Available in Mac OS X v10.2 and later.

Declared in ABTypedefs.h.

kABStringProperty

Indicates a CFString object.

Available in Mac OS X v10.2 and later.

Declared in ABTypedefs.h.

kABIntegerProperty

Indicates a CFNumber object representing an integer.

Available in Mac OS X v10.2 and later.

Declared in ABTypedefs.h.

kABRealProperty

Indicates a CFNumber object representing a real number.

Available in Mac OS X v10.2 and later.

Declared in ABTypedefs.h.

kABDateProperty

Indicates a CFDate object.

Available in Mac OS X v10.2 and later.

Declared in ABTypedefs.h.

kABArrayProperty

Indicates a CFArray object.

Available in Mac OS X v10.2 and later.

Declared in ABTypedefs.h.

kABDictionaryProperty

Indicates a CFDictionary object.

Available in Mac OS X v10.2 and later.

Declared in ABTypedefs.h.

`kABDataProperty`

Indicates a `CFData` object.

Available in Mac OS X v10.2 and later.

Declared in `ABTypedefs.h`.

`kABMultiStringProperty`

Indicates an `ABMultiValue` containing `NSString` objects.

Available in Mac OS X v10.2 and later.

Declared in `ABTypedefs.h`.

`kABMultiIntegerProperty`

Indicates an `ABMultiValue` containing `NSNumber` objects representing integers.

Available in Mac OS X v10.2 and later.

Declared in `ABTypedefs.h`.

`kABMultiRealProperty`

Indicates an `ABMultiValue` containing `NSNumber` objects representing real numbers.

Available in Mac OS X v10.2 and later.

Declared in `ABTypedefs.h`.

`kABMultiDateProperty`

Indicates an `ABMultiValue` containing `NSDate` objects.

Available in Mac OS X v10.2 and later.

Declared in `ABTypedefs.h`.

`kABMultiArrayProperty`

Indicates an `ABMultiValue` containing `NSArray` objects.

Available in Mac OS X v10.2 and later.

Declared in `ABTypedefs.h`.

`kABMultiDictionaryProperty`

Indicates an `ABMultiValue` containing `NSDictionary` objects.

Available in Mac OS X v10.2 and later.

Declared in `ABTypedefs.h`.

`kABMultiDataProperty`

Indicates an `ABMultiValue` containing `NSData` objects.

Available in Mac OS X v10.2 and later.

Declared in `ABTypedefs.h`.

Database Notifications

These are notifications published when something changes in the Address Book database. These notifications are not sent until [ABGetSharedAddressBook](#) (page 11) has been called.

```
CFStringRef kABDatabaseChangedNotification;  
CFStringRef kABDatabaseChangedExternallyNotification;
```

Constants

`kABDatabaseChangedNotification`

This process has changed the AddressBook database.

Available in Mac OS X v10.2 and later.

Declared in `ABGlobals.h`.

`kABDatabaseChangedExternallyNotification`

Another process has changed the AddressBook database. The following keys are included in the user-info dictionary of the notification: `kABInsertedRecords`, `kABUpdatedRecords`, and `kABDeletedRecords`. If the values for all the keys are `nil`, everything has changed, such as when the Address Book database is restored from a backup copy.

Available in Mac OS X v10.2 and later.

Declared in `ABGlobals.h`.

Document Revision History

This table describes the changes to *ABAddressBook C Reference*.

Date	Notes
2007-07-08	Updated for Mac OS X v10.5.
2006-05-23	Corrected typos.
2005-08-11	Corrected <code>ABCreateFormattedAddressFromDictionary</code> function result information.
2003-08-20	Revised for Mac OS X v10.3.
	Changed <code>ABCreateArrayOfAllGroups</code> to <code>ABCopyArrayOfAllGroups</code> (page 7). The former has been removed.
	Changed <code>ABCreateArrayOfAllPeople</code> to <code>ABCopyArrayOfAllPeople</code> (page 7). The former has been removed.
2003-03-01	First version of <i>ABAddressBook Reference for C</i> .

REVISION HISTORY

Document Revision History

Index

A

ABAddPropertiesAndTypes **function** [6](#)
ABAddRecord **function** [6](#)
ABAddressBookRef **data type** [14](#)
ABCopyArrayOfAllGroups **function** [7](#)
ABCopyArrayOfAllPeople **function** [7](#)
ABCopyArrayOfMatchingRecords **function** [8](#)
ABCopyArrayOfPropertiesForRecordType **function** [8](#)
ABCopyDefaultCountryCode **function** [9](#)
ABCopyRecordForUniqueId **function** [9](#)
ABCopyRecordTypeFromUniqueId **function** [9](#)
ABCreateFormattedAddressFromDictionary **function** [10](#)
ABGetMe **function** [10](#)
ABGetSharedAddressBook **function** [11](#)
ABHasUnsavedChanges **function** [11](#)
ABRemoveProperties **function** [12](#)
ABRemoveRecord **function** [12](#)
ABSave **function** [13](#)
ABSetMe **function** [13](#)
ABTypeOfProperty **function** [14](#)

D

Database Notifications [16](#)

K

kABArrayProperty **constant** [15](#)
kABDatabaseChangedExternallyNotification **constant** [17](#)
kABDatabaseChangedNotification **constant** [17](#)
kABDataProperty **constant** [16](#)
kABDateProperty **constant** [15](#)
kABDictionaryProperty **constant** [15](#)
kABErrorInProperty **constant** [15](#)

kABIntegerProperty **constant** [15](#)
kABMultiArrayProperty **constant** [16](#)
kABMultiDataProperty **constant** [16](#)
kABMultiDateProperty **constant** [16](#)
kABMultiDictionaryProperty **constant** [16](#)
kABMultiIntegerProperty **constant** [16](#)
kABMultiRealProperty **constant** [16](#)
kABMultiStringProperty **constant** [16](#)
kABRealProperty **constant** [15](#)
kABStringProperty **constant** [15](#)

P

Property Types [14](#)